

# INDOOR - COMPACT (COMPACT CEILING MOUNTED DUCT)

Model Name		FPDQ20APV1	FPDQ25APV1	FPDQ32APV1	FPDQ40APV1	FPDQ50APV1	FPDQ63APV1	
Power Supply	V/Ph/Hz	220-240V/1Phase/50Hz						
Cooling Capacity	Kw	2.2	2.8	3.6	4.5	5.6	7.1	
Power Consumption	W	72	75	78	93	180	196	
	With Water Drain Pump							
Air Flow Rate (Hi/Med Hi/Med/Mid Lo/Lo)	m3/min	8.7/8.1/7.6/7.0/6.5	9.0/8.5/8.0/7.5/7.0	8.3/7.4/6.8.6.3/5.8	10.0/9.2/8.5/8.0/7.2	13.5/12.0/11.5/11.0/10/0	17.5/16.0/15.0/14.0/13.0	
Sound Level (Hi/Med Hi/Med/Mid Lo/Lo)	dB(A)	27/26/25/24/23	28/27/26/25/24	29/28/27/26/25	33/32/31/30/29	33/32/31/30/29	37/35/33/32/31	
ESP (Hi/Std)	mm	10/0						
Unit Dimension (HxWxD)	mm	200 x 700 x 620				200 x 900 x 620		200 x 1100 x 620
Discharge Dimension (HxW)	mm	131 x 525				131 x 725		131 x 925
Unit Weight	kg	24				28		32
Piping Connections	Liquid Pipe/Gas Pipe	mm						
	High and Low Pressure Pipe	mm						
	Condensate Drain Pipe	mm						
Wired Remote Controller		PVC26(0.D.φ26/I.D.φ20) BRC1E632						