

# INDOOR - 3DI (INTELLIGENT 3D AIR AFLOW CEILING)

Model Name			FPDSQ20APV1	FPDSQ25APV1	FPDSQ32APV1	FPDSQ40APV1	FPDSQ50APV1	FPDSQ63APV1
Power Supply		V/Ph/Hz	220-240V/1Phase/50Hz					
Cooling Capacity		Kw	2.2	2.8	3.6	4.5	5.6	7.1
Power Consumption	With Water Drain Pump	W	28	29	32	49		54
Fan Mode/Cooling Mode	Air Flow Rate (Hi/Med Hi/Med/Mid Lo/Lo)	m3/min	7.2/6.8/6.3/5.8/5.4		8.3/7.4/6.8.6.3/5.8	10.0/9.2/8.5/8.0/7.2	13.5/12.0/11.5/11.0/10/0	17.5/16.0/15.0/14.0/13.0
	Sound Level (Hi/Med Hi/Med/Mid Lo/Lo)	dB(A)	29/27/26/25/23		32/31/29/27/25	36/34/32/30/28	36/35/33/31/30	37/35/33/32/31
ESP (Hi/Std)		mm	10/0					
Unit Dimension (HxWxD)		mm	200 x 700 x 620				200 x 900 x 620	200 x 1100 x 450
Discharge Dimension (HxW)		mm	131 x 525				131 x 725	131 x 925
Unit Weight		kg	17				20	23
Piping Connections	Liquid Pipe/Gas Pipe	mm	φ6.4/φ12.7					
	Condensate Drain Pipe	mm	PVC26(0.D.φ26/L.D.φ20)					
Wired Remote Controller			BRC1E632					